

ATTACHMENTS

HAMMERS

MODEL	IMPACT ENERGY CLASS	BLOWS PER MINUTE	OPERATING WEIGHT
H35S	300 ft-lbf	600 - 1,800	287 lbs
H45S	400 ft-lbf	780 - 1,800	551 lbs
H55S	600 ft-lbf	600 - 1,680	761 lbs
H65S	800 ft-lbf	720 - 1,740	860 lbs
B1	148 ft-lbf	800 - 1,400	183 lbs
B2	214 ft-lbf	700-1200	253 lbs
B4	273 ft-lbf	600-1100	351 lbs
B6	502 ft-lbf	500-900	571 lbs
B8	850 ft-lbf	400-800	772 lbs
B9	959 ft-lbf	400-800	1166 lbs

TILT ROTATORS

MODEL	MACHINE CLASS	OPTIMAL HYDRAULIC FLOW	WEIGHT RANGE
TRS6	6 Ton Excavators	12 - 21 Gal/Min	436 - 540 lbs
TRS8	7-10 Ton Excavators	12 - 20 Gal/Min	683 - 793 lbs

BROOMS

TYPE	SWEEPING WIDTH RANGES
Pick up Brooms	60 in - 72 in
Utility Brooms	58 in - 73 in
Angle Brooms	83 in - 126 in

COLD PLANERS

MODEL	WIDTH	OPTIMAL HYDRAULIC PRESSURE	OPTIMUM HYDRAULIC FLOW
PC104	14 in	3,330 psi	16-21 gal/min
PC105	18 in	2,320 - 3,480 psi	21-31 gal/min
PC305	18 in	3,330 - 4,000 psi	26-33 gal/min
PC306	24 in	3,330 - 4,000 psi	26-33 gal/min
PC310	39 in	4,000 psi	33 gal/min
PC404	18 in	2320 - 3480 psi	21-42 gal/min
PC406	24 in	4,000 psi	40 gal/min
PC408	30 in	4,000 psi	40 gal/min
PC412	47 in	4,000 psi	40 gal/min

MULCHERS

MODEL	DRUM WIDTH	OPTIMAL HYDRAULIC PRESSURE	OPTIMUM HYDRAULIC FLOW
HM316	62 in	2,900 - 4,061 psi	31-33 gal/min
HM416	59 in	2,900 - 5,077 psi	36-41 gal/min
HM418	67 in	2,900 - 4,061 psi	40-41 gal/min

AUGERS

MODEL	DRIVE SHAFT TORQUE AT MAX PRESSURE	OPTIMAL HYDRAULIC PRESSURE	REQUIRED HYDRAULIC FLOW
A11	815 lb ft	1,700 psi	20.0 gal/min
A23	1,700 lb ft	2,750 psi	21 gal/min
A41	3,040 lb ft	2,800 psi	20.0 gal/min
A68	5,040 lb ft	3,700 psi	34.0 gal/min

SNOW BLOWERS

MODEL	INTAKE WIDTH	OVERALL WIDTH	WEIGHT
SR115	60 in	62 in	934 lb
SR118	72 in	74 in	954 lb
SR121	72 in	86 in	974 lb
SR318	72 in	74 in	996 lb
SR321	85 in	86 in	1,016 lb
SR418	72 in	73 in	1,016 lb
SR421	85 in	86 in	1,016 lb

BRUSHCUTTERS

MODEL	WORKING WIDTH	OPTIMAL HYDRAULIC PRESSURE	REQUIRED HYDRAULIC FLOW
BR115	60 in	2,176 - 3,140 psi	15-17 gal/min
BR117	66 in	2,176 - 3,340 psi	15-21 gal/min
BR118	72 in	2,176 - 3,340 psi	15-21 gal/min
BR218	72 in	2,176 - 3,340 psi	20-26 gal/min
BR320	78 in	2,176 - 4,065 psi	20-34 gal/min



www.hopenn.com

Bloomingburg, NY 12721	Bronx, NY 10465	Holtsville, NY 11742	Poughkeepsie, NY 12603	Newington, CT 06111
783 Bloomingburg Road (845) 733-6400	699 Brush Avenue (718) 863-3800	660 Union Avenue LIE (Exit 62) (631) 758-7500	122 Noxon Road (845) 452-1200	225 Richard Street (860) 666-8401



CAT® SMALL AND MID-SIZED EQUIPMENT

SURPRISINGLY AFFORDABLE

www.hopenn.com





SKID STEER LOADERS

MODEL	NET HP	MACHINE ROC	OPERATING WEIGHT	PIN HEIGHT Bucket Pin Height at Max Lift
226D3	66	1,650	5,849	111"
232D3	66	2,000	6,514	118"
236D3	73	2,000	6,567	122"
250	73	2,916	7,829	124"
260	73	3,388	8,523	132"
270	99	3,914	8,296	133"
270 XE	121	4,372	10,487	135"

* ROC with additional counterweight which is H.O. Penn's standard configuration



COMPACT TRACK LOADERS

MODEL	NET HP	MACHINE ROC	OPERATING WEIGHT	PIN HEIGHT Bucket Pin Height at Max Lift
239D3	66	2,400	7,434	111"
249D3	66	2,700	7,831	118"
255	73	3,730	9,973	124"
265	73	4,280	10,948	132"
275	109	5,240	12,401	134"
275 XE	121	6,485	12,705	134"
285	109	6,795	13,497	146"
285 XE	121	6,880	13,669	146"

* ROC with additional counterweight which is H.O. Penn's standard configuration



ASHPALT COMPACTORS

MODEL	GROSS HP	OPERATING WEIGHT	COMPACTION WIDTH
CB1.7	24.7	3,538	35"
CB1.8	24.7	3,825	39"
CB2.5	48	4,960	39"
CB2.7	48	5,533	47"
CB4	48	7,971	51"



COMPACT WHEEL LOADERS

MODEL	NET HP	BUCKET RATING	OPERATING WEIGHT
903	45	0.8 – 1.3 yd ³	9,200
906	72.7	1.0 – 1.7 yd ³	12,898
907	72.7	1.0 – 1.7 yd ³	12,944
908	72.7	1.0 – 2.0 yd ³	14,822
910	99	1.7 – 3.9 yd ³	18,085
914	99	2.0 – 3.9 yd ³	19,740
920	121	2.2 – 4.6 yd ³	23,713

MINI-EXCAVATORS



MODEL	NET HP	OPERATING WEIGHT	MAX DIG DEPTH
300.9	13	2,061	5'8"
301.5	21	3,913	8'4"
301.7 CR	21	4,222	8'4"
301.8	21	4,473	8'5"
302	21	4,987	8'5"
302.7 CR	23	6,858	8'6"
303 CR	23	6,924	9'8"
303.5	23	8,350	10'2"
304	45	8,875	11'6"
305 CR	45	12,455	12'0"
306 CR	55	15,755	13'6"
307.5	55	17,905	15'2"
308 CR	69	20,678	15'2"
309 CR HF	69	21,642	15'2"
310	69	22,502	17'1"

* Dig depth based on long stick, H.O. Penn's standard configuration



BACKHOE LOADERS

MODEL	NET HP	DIG DEPTH
415IL	69	N/A
416	70/86	14'-17'7"
420	92	14'-17'7"
420XE	92	14'-17'7"
430	107	15'2"-19'3"
440	104	15'6"-19'3"
450	131	17'-21'1"



DOZERS

MODEL	NET HP	OPERATING WEIGHT
D1	80	17,855
D2	92	18,382
D3	104	20,640



SMALL EXCAVATORS

MODEL	NET HP	OPERATING WEIGHT	MAX DIG DEPTH
313 GC	73	30,900	19'10"
315 GC	98	34,000	19'7"
315	108	34,000	19'7"
317 GC	119	39,780	21'8"
317	133	39,780	21'8"



SMALL WHEEL LOADERS

MODEL	NET HP	BUCKET RATING	OPERATING WEIGHT
926	168	2.5 – 6.5 yd ³	28,852
930	168	2.7 – 6.5 yd ³	32,005
938	188	3.3 – 6.5 yd ³	37,379



TELEHANDLERS

MODEL	HP	RATED LOAD CAPACITY	MAX LIFT HEIGHT
TH0642	74	6,000	42'
TH082	115	8,000	42'
TH1055	115	10,000	54'6"
TH1255	115	12,000	54'6"



hopenmachinery



HOPennCat



FAMILY OWNED FOR
THREE GENERATIONS