

**BACKHOE LOADERS**

MODEL	415 IL	416	420	420 XE	428	430	432	434	440	450
Engine	C3.6	C3.6	C3.6	C3.6	C3.6	C3.6	C3.6	C3.6	C3.6	C3.6
Net Power (hp)	69	69/85	91/101	91/101	70	107	92	92	115	130
Operating Weight - Maximum (lb)	17,637	24,251	24,251	24,251	24,251	24,251	24,251	25,353	29,321	29,321
<b>BACKHOE</b>										
Dig Depth - Standard Stick (ft)	NA	14.0	14.0	14.0	15.7	15.2	15.7	15.8	15.5	17.0
Dig Depth - Extendable Stick (ft)	NA	17.7	17.7	17.7	18.7	19.3	20.1	18.9	19.3	21.1
Bucket Dig Force - Standard (lbf)	NA	13,291	14,431	14,431	14,263	16,163	14,263	14,254	16,890	17,784
Stick Dig Force - Standard (lbf)	NA	7,278	9,786	9,786	8,145	10,086	9,628	8,277	10,199	11,904
Loading Height - Standard (ft)	NA	12.2	12.2	12.2	13.1	13.3	13.1	12.9	14.0	14.1
<b>LOADER</b>										
Bucket Capacity - General Purpose (yd³)	1.25	1.25	1.31	1.31	1.31	1.31	1.25	1.70	1.75	1.75
Dump Height Max Angle (ft)	9.1	9.1	9.2	9.2	9.1	9.2	9.2	8.9	8.1	9.0
Lift Capacity at Full Height (lb)	6,530	6,530	7,245	7,245	8,219	7,245	8,300	9,617	8,782	8,886

**WHEEL LOADERS**

COMPACT					SMALL					
MODEL*	903	906	907	908	910	914	920	926	930	938
Engine	C1.7	C2.8	C2.8	C2.8	C3.6	C3.6	C3.6	C7.1	C7.1	C7.1
Gross Power (hp)	48.0	74.7	74.7	74.7	110.0	110.0	121.0	170	170	191
Operating Weight (lb)	9,200	12,628	12,765	14,617	18,102	19,103	21,742	27,972	31,124	35,528
Bucket Cap. (yd³)	0.8-1.3	1.0-2.0	1.0-2.0	1.0-2.0	1.7-4.6	1.7-4.6	1.7-4.6	2.5-6.5	2.5-6.5	2.5-6.5
Breakout Force (lbf)	6,294	11,233	11,232	13,791	14,857	16,214	18,691	25,481	28,405	29,028
Full-Turn Tipping Load (lb)	5,516	8,534	8,606	9,414	10,795	11,603	13,280	16,682	19,637	22,292

\*Based on standard lift, general purpose bucket and coupler.

MEDIUM											
MODEL	950 GC	950	962	966 GC	966	966 XE	972	972 XE	980	980 GC	980 XE
Engine	C7.1	C7.1	C7.1	C9.3B	C9.3B	C9.3B	C9.3B	C9.3B	C13	C13	C13
Rated Power (hp)	225	249	269	294	321	321	339	339	420	420	420
Operating Wt. (lb)	41,544	42,461	44,469	48,018	51,124	51,124	54,858	54,858	66,877	65,610	66,877
Bucket Cap. (yd³)	3.75-5.75	3.30-12.00	3.30-12.00	4.25-9.25	3.75-15.50	3.75-15.50	3.75-18.25	3.75-18.25	5.25-19.00	5.75-19.00	5.25-19.00
Breakout Force (lbf)	34,638	40,690	42,489	36,974	38,999	38,999	44,072	44,072	51,008	47,660	51,008
Full-Turn Tipping Load (lb)	25,875	26,369	27,529	32,233	32,727	32,727	35,919	35,919	43,432	42,441	43,432

MEDIUM (CONT.)			LARGE							
MODEL	982	982 XE	MODEL	986	988	988 XE	990	992	993	995
Engine	C13	C13	Engine	C15	C18	C18	C27	C32B	C32B	3516E
Rated Power (hp)	432	432	Net Power (hp)	373	538	538	699	814	974	1739
Operating Wt. (lb)	78,264	78,264	Operating Wt. (lb)	97,785	112,574	116,362	178,517	233,430	294,687	540,055
Bucket Cap. (yd³)	6.25-22.50	6.25-22.50	Bucket Cap. (yd³)	6.5-13.5	6.2-17.0	6.2-17.0	9.7-19.5	15.0-32.0	16.0-31.0	22.3-57.0
Breakout Force (lbf)	59,060	59,060	Breakout Force (lbf)	72,620	98,241	98,315	132,617	157,125	171,522	334,077
Full-Turn Tipping Load (lb)	46,526	46,526	Full-Turn Tipping Load (lb)	55,572	79,435	67,299	97,401	136,309	150,231	302,893



# Cat® SPEC GUIDE

## 2026 POCKET REFERENCE



For more information about Cat Equipment, contact us at **844-CAT-1923** or visit **www.hopenn.com**

**DOZERS**

SMALL			
MODEL	D1	D2	D3
	NEXT GEN	NEXT GEN	NEXT GEN
Engine	C3.6	C3.6	C3.6
Net Power (hp)	80	92	104
Operating Weight (lb)	17,855	18,382	20,640
Blade Capacity (yd³)	1.99	2.59	2.86

MEDIUM						
MODEL	D4	D5	D6	D6 XE	D7	D8
	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN
Engine	C4.4	C7.1	C9.3B	C9.3B	C9.3B	C15
Net Power (hp)	130	170	215	215	265	354
Oper. Wt. (lb)	29,258	42,263	50,733	51,333	65,644	87,600
Blade Cap. (yd³)	4.26	5.50	7.50	7.50	10.00	13.00

LARGE			
MODEL	D9	D10	D11/D11 CD
Engine	C18	C27	C32
Net Power (hp)	452	600	850
Oper. Wt. (lb)	110,225	154,888	229,800
Blade Cap. (yd³)	21.70	24.20	45.00

**TRACK LOADERS**

MODEL	953	963	973
	NEXT GEN	NEXT GEN	NEXT GEN
Engine	C7.1	C7.1	C9.3
Net Power (hp)	160	202	275
Oper. Wt. (lb)	34,594	44,881	63,900
Rated Bucket Cap. (yd³)	2.4	3.2	4.2
Bucket Width (in)	97.8	102.8	117.0

**TELEHANDLERS**

MODEL	TH0642	TH0842	TH1055	TH1255
Engine	C3.6	C3.6	C3.6	C3.6
Gross Power (hp)	74	74/115	74/115	74/115
Oper. Wt. (lb)	21,647	23,366	29,838	31,238
Rated Cap. (lb)	6,000	8,000	10,000	12,000
Max. Lift Height (ft)	42.1	42.1	54.6	54.6

**TECHNOLOGY SOLUTIONS**  
Cat® Technology increases your accuracy and productivity.



Scan the QR Code with your smart phone to learn more about Cat Technology.

**HYDRAULIC EXCAVATORS**

**MINI**

MODEL	300.9D	301.5	301.7 CR	301.8	302 CR	302.7 CR	303 CR	303.5 CR	304	305 CR	306 CR	307.5	308 CR FB	308 CR	308 CR VAB	309 CR	309 CR VAB	310
		NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN
Engine	31NV70	C1.1	C1.1	C1.1	C1.1	C1.1 Turbo	C1.1 Turbo	C1.7	C1.7 Turbo	C1.7 Turbo	C2.4 Turbo	C2.4 Turbo	C2.8 Turbo	C2.8 Turbo	C2.8 Turbo	C2.8 Turbo	C2.8 Turbo	C2.8 Turbo
Net Power (hp)	13.0	21.0	21.0	21.0	21.0	23.6	23.6	23.6	45.0	45.0	55.9	54.8	69.5	69.5	69.5	69.5	69.5	69.5
Operating Weight (lb)	2,061	3,913	4,222	4,473	4,987	6,725	7,817	9,239	9,867	12,688	15,766	17,905	18,659	20,771	21,080	20,870	22,094	22,859
Stick Digging Force (lbf)	1,011	1,843	2,136	2,540	2,540	3,102	3,732	4,249	4,721	6,362	6,632	8,504	9,285	9,509	9,509	9,500	9,509	11,060
Bucket Digging Force (lbf)	2,000	3,169	3,642	4,406	4,406	5,238	6,385	7,419	8,588	11,061	11,578	12,272	12,241	13,946	13,946	13,943	13,946	17,459
Blade Width (in)	28.0	39.0	39.0	39.0	42.9	61.8	61.0	70.1	66.9	78.0	78.0	90.6	90.6	90.6	90.6	97.0	97.0	97.0
Max. Digging Depth (in)	68.0	100.0	100.0	101.2	101.2	106.7	116.1	122.4	138.2	144.5	162.0	182.8	185.0	182.8	150.2	182.8	150.2	205.2

**SMALL**

**MEDIUM**

**LARGE**

MODEL	313 GC	313	315 GC	315	317 GC	317	319	320 GC	320	323	325	326	330 GC	330	335
	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN
Engine	C3.6	C3.6	C3.6	C3.6	C3.6	C4.4	C3.6	C4.4e TA	C4.4e TA	C7.1e TA	C4.4	C7.1	C7.1	C7.1	C7.1
Net Power (hp)	73	108	98	108	119	130	133	146	172	172	172	202	202	273	273
Op. Weight (lb)	30,400	30,400	34,000	34,000	38,100	40,200	44,100	48,300	48,300	54,900	62,800	56,400	67,900	69,200	77,000
Max. Digging Depth (ft)	19.8	19.8	19.6	19.6	21.0	21.0	21.5	22.0	22.1	22.1	22.0	22.3	23.8	23.9	22.1

MODEL	336	340	350	352 Fixed Gauge Undercarriage	352 Variable Gauge Undercarriage	374	395
	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN
Engine	C7.1	C9.3B	C9.3B	C13B	C13B	C15	C18
Net Power (hp)	302	347	414	443	443	485	543
Operating Wt. (lb)	81,200	82,700	105,100	111,300	113,500	158,100	207,300
Max. Digging Depth (ft)	27.0	27.0	27.0	27.0	27.4	28.1	31.7

\*Caterpillar also provides excavator-based, specialty equipment solutions in sizes ranging from the 313 through the 395. Consult our dealership for more information.

**SKID STEER LOADERS**

MODEL	226D3	232D3	236D3	250	260	270	270 XE
				NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN
Engine	C2.2 CRDI	C2.2 CRDI	C2.2T	C2.8T	C2.8T	C3.6TA	C3.6TA
Gross Power (hp)	67.1	67.1	67.2	74.0	74.0	100.0	121.0
Operating Weight (lb)	5,849	6,514	6,572	7,829	8,523	10,441	10,847
Rated Operating Cap. (lb)	1,550	1,900	1,820	2,689	3,160	3,557	4,015
Loader Hyd. Power (hp)	35.5	35.5	39.0	46.4	46.4	46.4	46.4
Bucket Pin Height at Max Lift (in)	110.9	118.1	122.9	124.0	132.5	133.5	135.4
Speed Fwd/Rev - 1 or opt. 2 spd (mph)	7.6/11.1	7.6/11.1	7.5/11.4	8.0/10.5	7.7/11.1	6.6/9.6	7.3/10.6

**MOTOR GRADERS**

MODEL	120 GC/ 120GC AWD	120/ 120 AWD	140 GC/ 140 GC AWD	140/ 140 AWD-LVR	140/ 140 AWD	150/ 150 AWD	160/ 160 AWD	14	16	18	24
Engine	C4.4	C7.1	C7.1	C7.1	C7.1	C9.3	C9.3	C13	C13	C13	C27
Net Power (hp) (1st Gear)	154/163	140/146	176/196	248	248	200/210	221/231	238	290	304	535
Blade Width (ft)	10, 12, 14	12, 14	12, 14	12	12	12, 14	12, 14, 16	14, 16	16	18	24
Operating Weight - Typically Equipped (lb)	31,958/ 33,162	35,871/ 37,657	40,488/ 42,119	42,543	42,543	43,950/ 45,917	45,547/ 47,514	57,250	71,454	74,324	165,314
Top Speed (mph) (Fwd)	25.8	30.1	29.0	30.1	30.1	29.0	29.5	32.1	32.1	32.1	26.0
Top Speed (mph) (Rev)	16.3	23.7	23.0	23.7	23.7	23.0	23.3	25.4	25.4	25.3	25.6

**COMPACT TRACK LOADERS**

MODEL	239D3	249D3	255	265	275	275 XE	285	285 XE
			NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN
Engine	C2.2 CRDI	C2.2 CRDI	C2.8T	C2.8TA	C3.6TA	C3.6TA	C3.6TA	C3.6TA
Gross Power (hp)	67.1	67.1	74.0	74.0	111	121	111	121
Operating Weight (lb)	7,434	7,831	9,578	10,492	12,401	12,705	13,497	13,699
Loader Hydr. Power (hp)	35.5	35.5	46.4	46.4	46.4	46.4	46.4	46.4
Tipping Load (lb)	4,370	4,970	7,140	8,066	11,874	12,015	12,745	12,915
ROC @ 35% Tip. Load (lb)	1,530	1,740	2,499	2,823	4,156	4,205	4,461	4,520
Bucket Pin Height at Max Lift (in)	111.2	118.2	124.0	132.0	134.4	134.4	146.6	146.6

**WHEELED EXCAVATORS**

MODEL	M314	M315	M316	M318	M319	M320	M322
	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN	NEXT GEN
Engine	C3.6	C4.4	C4.4	C4.4	C4.4	C4.4	C7.1
Net Power (hp)	134	148	148	174	174	174	174
Max Travel Speed (mph)	23	21.7	21.7	21.7	21.7	21.7	18.6
Operating Weight (lb)	39,683	39,680	36,400	43,980	46,407	46,740	52,911

Because specifications are subject to change without notice, check with our dealership or visit [cat.com](http://cat.com) for the latest equipment information.

©2026 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Yellow", the "Power Edge" and Cat "Modern Hex" trade dress and Product Link, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission. ©2026 High Velocity Communications Inc.